



MySQL Database

With PHP, you can connect to and manipulate databases.
MySQL is the most popular database system used with PHP.

What is MySQL?

MySQL is a database system used on the web

MySQL is a database system that runs on a server

MySQL is ideal for both small and large applications

MySQL is very fast, reliable, and easy to use

MySQL uses standard SQL

MySQL compiles on a number of platforms

MySQL is free to download and use

MySQL is developed, distributed, and supported by Oracle Corporation

MySQL is named after co-founder Monty Widenius's daughter: My



MySQL Database

The data in a MySQL database are stored in tables. A table is a collection of related data, and it consists of columns and rows.

Databases are useful for storing information categorically. A company may have a database with the following tables:

- Employees
- Products
- Customers
- Orders

PHP + MySQL Database System

PHP combined with MySQL are cross-platform (you can develop in Windows and serve on a Unix platform)

Database Queries: A query is a question or a request.

We can query a database for specific information and have a recordset returned.



MySQL Database

Database Queries

A query is a question or a request.

We can query a database for specific information and have a recordset returned.

Look at the following query (using standard SQL):

```
SELECT LastName FROM Employees
```

The query above selects all the data in the "LastName" column from the "Employees" table.

Download MySQL Database

If you don't have a PHP server with a MySQL Database, you can download it for free here: <http://www.mysql.com>

Facts About MySQL Database

MySQL is the de-facto standard database system for web sites with HUGE volumes of both data and end-users (like Facebook, Twitter, and Wikipedia).



MySQL Database

PHP Connect to MySQL

PHP 5 and later can work with a MySQL database using:

MySQLi extension (the "i" stands for improved)

PDO (PHP Data Objects)

Earlier versions of PHP used the MySQL extension. However, this extension was deprecated in 2012.



MySQL Database

Should I Use MySQLi or PDO?

If you need a short answer, it would be "Whatever you like".

Both MySQLi and PDO have their advantages:

PDO will work on 12 different database systems, whereas MySQLi will only work with MySQL databases.

So, if you have to switch your project to use another database, PDO makes the process easy. You only have to change the connection string and a few queries. With MySQLi, you will need to rewrite the entire code - queries included.

Both are object-oriented, but MySQLi also offers a procedural API.

Both support Prepared Statements. Prepared Statements protect from SQL injection, and are very important for web application security.



MySQL Database

MySQLi Installation

For Linux and Windows: The MySQLi extension is automatically installed in most cases, when php5 mysql package is installed.

For installation details, go

to: <http://php.net/manual/en/mysqli.installation.php>

PDO Installation

For installation details, go

to: <http://php.net/manual/en/pdo.installation.php>

MySQL Database

Open a Connection to MySQL

Before we can access data in the MySQL database, we need to be able to connect to the server:

Example (MySQLi Object-Oriented)

```
<?php
```

```
$servername = "localhost";
```

```
$username = "username";
```

```
$password = "password";
```

```
// Create connection
```

```
$conn = new mysqli($servername, $username, $password);
```

```
// Check connection
```

```
if ($conn->connect_error) {
```

```
    die("Connection failed: " . $conn->connect_error);
```

```
}
```



MySQL Database

Note on the object-oriented example above:

\$connect_error was broken until PHP 5.2.9 and 5.3.0. If you need to ensure compatibility with PHP versions prior to 5.2.9 and 5.3.0, use the following code instead:

```
// Check connection
if (mysqli_connect_error()) {
    die("Database connection failed: " . mysqli_connect_error());
}
```



MySQL Database

Example (MySQLi Procedural)

```
<?php
```

```
$servername = "localhost";
```

```
$username = "username";
```

```
$password = "password";
```

```
// Create connection
```

```
$conn = mysqli_connect($servername, $username, $password);
```

```
// Check connection
```

```
if (!$conn) {
```

```
    die("Connection failed: " . mysqli_connect_error());
```

```
}
```

```
echo "Connected successfully";
```

```
?>
```



MySQL Database

Example (PDO)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
try {
    $conn = new PDO("mysql:host=$servername;dbname=myDB",
$username, $password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);
    echo "Connected successfully";
} catch(PDOException $e) {
    echo "Connection failed: " . $e->getMessage();
}
?>
```



MySQL Database

Note: In the PDO example above we have also **specified a database (myDB)**. PDO require a valid database to connect to. If no database is specified, an exception is thrown.

Tip: A great benefit of PDO is that it has an exception class to handle any problems that may occur in our database queries. If an exception is thrown within the `try{ }` block, the script stops executing and flows directly to the first `catch(){ }` block.



MySQL Database

Close the Connection

The connection will be closed automatically when the script ends. To close the connection before, use the following:

MySQLi Object-Oriented:

```
$conn->close();
```

MySQLi Procedural:

```
mysqli_close($conn);
```

PDO:

```
$conn = null;
```